



## Legend Uniform Semi-automatic, uniform case sealer

### Maximizes Productivity

Seals uniform cases with a belt speed of up to 80' per minute

### Simplifies Maintenance

Operator friendly self tensioning belt systems require no manual adjustments and reduce wear

### Production Versatility

Features offset tape heads which allow for a minimum case height of 2 5/8"

### Robust Design

7 Gauge steel mast and 12 Gauge welded steel head and structural platform

# Legend Uniform Semi-automatic, uniform case sealer

The Legend Uniform is an operator fed, semi-automatic, uniform, industrial grade case sealer designed to top and bottom seal corrugated cases. The Legend Uniform features offset tape heads which allow for a minimum case height of 2 5/8".

## Features and benefits

### ■ Performance

- Operator friendly self tensioning belt systems require no manual adjustments and reduce wear.
- Continuous belt drive speed of 80' per minute

### ■ Versatility

- Compact footprint
- Expansive case range
- Quick changeover
- Converts from 2 to 3" tape in the field
- Height adjustment with counter balanced flat spring with slide and lock mechanism
- Width adjustment has self-centering, interlocked guide rails with steel lock knob

### ■ Durability

- Ideal for 4/7 operations
- Powerful 1/3 HP high efficiency motor drive system
- 7 gauge steel mast & stainless steel side rails
- 12 gauge welded steel head and structural platform

### ■ Safety

- Single mast design allows operator clear path in machine
- Tape cartridge features patented locking knife guard

## Optional equipment

- Top Squeezers
- Pack tables
- Casters
- Top three flap folder
- Increased conveyor height
- 34" high case capability (type II)
- Mirror Image
- Jet Printer Adapter
- 3 phase electrics
- Spare parts kit
- 3" wide PST ( top & bottom)
- Spare cartridge
- Secondary stop button
- NEMA 12 electrical package
- NEMA 4 wiring-enclosure & switch



## CaseLocker™ 60 series tape cartridges

- Patented locking knife guard system allows the blade to be exposed only when the rollers are depressed
- Telescoping tape core allows for varying tape core sizes
- Patented tool-less removal of blades and wipe rollers
- Processes weak corrugated
- No lubrication points
- Utilizes link bar and knife arm bearings for added strength



## Legend Uniform Technical Specifications

<b>Power</b>	110 VAC, single phase, 60 cycle Other voltages available Contact Loveshaw for details
<b>Air</b>	NA
<b>Operating Speed</b>	Continuous belt drive; 80' per minute (24.4/min.) - production rate depends on box size and operator dexterity
<b>Case Range</b>	Length: 4.5" - infinite Width: 4.5" - 20" Height: 2 5/8" - 24"
<b>Machine Dimensions</b>	55 5/16" (141 cm) Length 30 3/16" (94.77cm) Width 61 3/16" (160.50cm) Height
<b>Weight</b>	230 lbs. (104 kg.), uncrated
<b>Conveyor Height</b>	22 1/4" to 30 1/4" Standard Consult factory for other heights
<b>3-2-1 Limited Warranty</b>	3 Year - Tape Cartridges 2 Year - Complete drive system, motor/gear reducer 1 Year - All other parts except for wear and moving parts
<b>Closure Material</b>	Pressure sensitive tape

The company reserves the right to make technical alterations without prior notification.  
© 2019 Signode Industrial Group, LLC / SPD 0000 Rev 191015 / [www.Signode.com](http://www.Signode.com)

 **SIGNODE**  
Loveshaw/Little David  
1-800-572-3434