

LITTLE DAVID

CASE FORMER SP-304R BO

BOTTOM-ONLY – RANDOM CASE FORMING



FORMING SOLUTIONS FOR THE REAL WORLD

The Little David® **SP-304R BO** is a semi-automatic random case erecting solution capable of facilitating the forming of up to 12 cases per minute. The **SP-304R BO** is an ideal machine for erecting and bottom-sealing random cases for those utilizing a variety of box sizes.

FEATURES OF THE SP-304 INCLUDE:

Ergonomic - reduces operator fatigue and repetitive motion syndrome

Extended case range for multiple case sizes

Portable - ideal for short case runs and frequent changeover

Reduces labor while maximizing operator efficiency

Replaces hand taping boxes.

Case Capacity:

Length: 8" - max. based on anvil

Width: 4.5" - 20"

Height: 3.5" - infinite

Processes 32 ect single wall to 44 ect double wall boxes.

PERFORMANCE & DESIGN FEATURES:

Universal folding bar folds the bottom flaps



LITTLE DAVID

SP-304R BO

LITTLE DAVID * PERFORMANCE & DESIGN FEATURES:

- The **SP-304R BO** incorporates an anvil pack table station. This provides a table that allows the operator to form the box before sealing the bottom.
- The **SP-304R BO** random side belt drives provide a positive drive for the box from the pack anvil station thru the bottom major folding bars to the tape cartridge.
- The **SP-304R BO** incorporates adjustable side drive limiters.
- The **SP-304R BO** incorporates a movable control station. The control station can be placed to any metal surface of the machine. This versatility allows the operator to place the controls of the machine on both sides for standard and mirror image flow.



SPECIFICATIONS:

Power Requirements:

Standard Voltage: 120/1/60 with 15 amp dedicated service.

*Optional voltages are available, please consult factory.

Air Requirements:

3 SCFM @ 45 psi

Operating Speed:

Standard belt speed: 72 ft/min

Closure Material:

Pressure Sensitive Tape

Weight:

570 lbs. (258 kg.), uncrated

CASE CAPACITY:

Length: 8" min. / max. based on anvil

Width: 4.5" min. (2" tape)

5.5" min. (3" tape)

20.0' max.

Height: 3 1/2" min.

MACHINE DIMENSIONS:

Height:

29.63" @ 24.25" conveyor height

Length including pack table:

31.77" overall - (base machine)


79.77" overall - (w standard 48" anvil)

Width:

37.65"

Conveyor height:

24.25" to 29.25" – Standard



DISTRIBUTED BY:

LOVESHAW

2206 East Turnpike
P.O. Box 83, South Canaan, PA 18459
Tel: (570) 937-4921 Fax: (570) 937-3229
Toll Free: (800) 572-3434

LOVESHAW Europe

Unit 9 Brunel Gate
West Portway Industrial Estate
Andover, Hampshire, England SP10 3SL
Tel: (1264) 357511 Fax: (1264) 355963

Printed in America

© 2012 LOVESHAW

www.youtube.com/loveshaw

http://twitter.com/loveshaw

