

Starview Packaging Machinery, Inc. Toll free: 1-888-278-5555 / www.starview.net

## **EXPERIENCE THE STARVIEW ADVANTAGE:**

- A wide range of standard and custom size machines available to match customer requirements.
- The only pendant mounted color touch screen HMI in the industry for the ultimate in operator convenience and accessibility.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to process information from the machine.
- Fully adjustable vacuum motor speed and oven power using an on-screen touch bar graph to provide precise film temperature and vacuum control.
- Machine operating recipe storage including all timer and bar graph settings with memory for up to 99 different recipes for operator recall of proven set-ups for complex products.
- Automatic template infeed and optional automatic outfeed designed to shorten loading and unloading times and reduce labor input.
- Industry leading design, construction, features and customer support.

## **DESCRIPTION:**

**Starview's ASP Series** skin packaging machines are designed for low to medium volume applications. ASP machines incorporate a stationary heating system with instant on/off heaters. ASP skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. An automatic in-feed table with traveling template loader, out-feed table and impulse type hot wire cut-off are all standard. A multi-stage vacuum system for complex parts is included as a part of the HMI. A film temperature sensor that overrides the PLC heat timer for consistent film heating is standard.

**Starview's ASP** skin packaging machines can be equipped with an optional automatic overhead out-feed system. The PLC can be used to advance an optional conveyor to remove finished skin packages from the work area.



## **SPECIFICATIONS:**

	ASP-1824	ASP-2430	ASP-2436
Max card size:	18" x 24"	24" x 30"	24" x 36"
Max product height:	6"	6"	6"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Average cycle speed:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical:	208-240 Volts / 3 PH / 32 Amps	208-240 Volts / 3 PH / 55 Amps	208-240 Volts / 3 PH / 70 Amp

	ASP-3036	ASP-3048	ASP-3648
Max card size:	30" x 36"	30" x 48"	36" x 48"
Max product height:	6"	6"	6"
Heating system:	Quartz impulse	Quartz impulse	Quartz impulse
Average cycle speed:	15-60 seconds	15-60 seconds	15-60 seconds
Electrical:	208-240 Volts / 3 PH / 84 Amps	208-240 Volts / 3 PH / 106 Amps	208-240 Volts / 3 PH / 125 Amp

Specifications and model availability are subject to change without notice.

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.

MEMBER



view a video about these products on







## **Leading the industry** With innovative packaging machine designs for:

Skin Packaging and Die Cutting · Food Tray Packaging · Thermoforming / Vacuum Forming **Customized Packaging Equipment · Systems with Automation & Integration** 

Blister & Clamshell Sealing · Medical / Pharmaceutical Packaging · Stretch Pak Packaging

1840 St. Regis Blvd. Dorval, Quebec H9P 1H6 Tel: 514-920-0100 Fax: 514-920-0092 Toll Free: 888-278-5555

www.starview.net sales@starview.net